

**WETNESS INDICATOR FOR ALERTING A WEARER TO URINATION**Background of the Invention

5 The present invention relates generally to absorbent articles, and more particularly to a wetness indicator for use in absorbent articles to alert a wearer to urination.

10 Disposable absorbent articles such as diapers, training pants, other child care products, other infant care products and adult care products are highly absorbent and efficiently pull moisture away from the wearer, reducing skin irritation caused by prolonged wetness exposure. However, because these articles are so absorbent, wearers may not realize they have urinated, particularly if they are inexperienced toddlers who may not recognize the meaning of body sensations associated with urination. Thus, the wearer may not recognize their urination control failure or be aware the article should be changed. Many parents  
15 believe that children must be given a signal such as feeling uncomfortable and wet to facilitate toilet training by making the child more aware that the act of urination has occurred. However, some parents worry about the possibility of skin irritations and rashes caused by prolonged wetness against the skin if the articles are less absorbent to allow the child to sense wetness.

20 Some prior absorbent articles intended for toilet training include means for alerting a child that urination has occurred without leaving a substantial amount of wetness against the skin. One such prior absorbent article includes a temperature changing element which allows the wearer to feel a change in temperature, alerting them after urination has occurred. Another example  
25 includes an element which changes size after urination, expanding directly toward the wearer's crotch region. Still another example has high initial surface moisture immediately following urination but pulls moisture away from the wearer shortly thereafter.

30 Although there has been progress in articles for alerting a wearer to urination, there continues to be a need for articles such as toilet training aids

which alert wearers to urination without allowing the skin to become wet.

### Summary of the Invention

Generally, a wetness indicator of the present invention for alerting a  
5 wearer to urination comprises a liquid permeable enclosure having a liquid  
absorbent body therein. The absorbent body absorbs liquid in the presence  
thereof and applies hydraulic pressure to the enclosure upon absorption of a  
preselected amount of liquid. The enclosure limits expansion of the absorbent  
body, stiffening the wetness indicator as liquid is absorbed. The wetness  
10 indicator has a first stiffness when dry and a second stiffness greater than the first  
stiffness upon absorption of the preselected amount of liquid.

The invention is further directed to a garment having an inner  
surface facing a wearer when wearing the garment and a wetness indicator  
generally as set forth above positioned relative to the inner surface for alerting the  
15 wearer when the inner surface becomes wet with liquid.

Other features of the present invention will be in part apparent and  
in part pointed out hereinafter.

### Brief Description of the Drawings

20 Fig. 1 is a perspective of training pants having a wetness indicator of  
the present invention therein;

Fig. 2 is a schematic top plan of unfolded training pants of a first  
embodiment;

Fig. 3 is an enlarged schematic front elevation of a wetness  
25 indicator of the present invention partially broken away to show interior details;

Fig. 4 is a schematic section of the wetness indicator taken in the  
plane of line 4-4 of Fig. 3;

Fig. 5 is a schematic top plan of unfolded training pants of a second  
embodiment;

Fig. 6 is a schematic top plan of unfolded training pants of a third embodiment;

Fig. 7 is a schematic top plan of unfolded training pants of a fourth embodiment; and

5 Fig. 8 is an enlarged schematic section of the training pants of the fourth embodiment taken in the plane of line 8-8 of Fig. 7.

Corresponding reference characters indicate corresponding parts throughout the several views of the drawings.

10 Definitions

Within the context of this specification, each term or phrase below includes the following meaning or meanings:

15 "Attached to" refers to the joining, adhering, connecting, bonding, or the like, of two elements. Two elements will be considered to be attached to one another when they are attached directly to one another or indirectly to one another, such as when each is directly attached to intermediate elements.

"Bonded" refers to the joining, adhering, connecting, attaching, or the like, of two elements. Two elements will be considered to be bonded together when they are bonded directly to one another or indirectly to one another, such as  
20 when each is directly bonded to intermediate elements.

"Layer" when used in the singular can have the dual meaning of a single element or more than one element.

"Superabsorbent" refers to a water-swellable, water-insoluble organic or inorganic material capable, under the most favorable conditions, of  
25 absorbing at least about fifteen times its weight and, more desirably, at least about thirty times its weight in an aqueous solution containing 0.9 weight percent sodium chloride. The superabsorbent materials can be natural, synthetic and modified natural polymers and materials, or a combination of such materials. In addition, the superabsorbent materials can be inorganic materials, such as silica  
30 gels, or organic compounds such as cross-linked polymers.

Detailed Description of the Preferred Embodiments

Referring now to the drawings and more particularly to Fig. 1, a pair of toilet training pants, or more generally an absorbent article, is designated in its entirety by the reference numeral 21. The pants have a waist opening 25 and two  
5 leg openings 27. Where the pants 21 are worn, a crotch region, generally designated 31 and located generally between the leg openings 27, is generally positioned between the legs of the wearer. A front 33 of the training pants 21 extends generally upward from the crotch region 31, partially covering a lower abdomen of the wearer. A back 35 of the training pants 21 opposite the front 33  
10 extends generally upward from the crotch region 31 to cover a buttocks of the wearer. The training pants 21 include an inner surface 36 facing the wearer and an outer surface 37 facing away from the wearer.

Various materials and methods for constructing training pants are disclosed in PCT Publication No. WO 00/37009 by Fletcher et al. published June  
15 29, 2000; U.S. Patent No. 4,940,464 issued July 10, 1990, to Van Gompel et al.; and U.S. Patent No. 5,766,389 issued June 16, 1998, to Brandon et al.; all of which are hereby incorporated by reference. An example of such training pants is marketed under the mark PULL-UPS® training pants by Kimberly-Clark Corporation of Neenah, Wisconsin.

20 A wetness indicator for alerting a wearer to urination, generally designated by 39, is positioned generally between the leg openings 27 of the training pants 21. It should be understood that the wetness indicator 39 may be positioned elsewhere than in the crotch region 31 without departing from the scope of the present invention. It is envisioned that the position of wetness  
25 indicator 39 within the crotch region 31 may be different depending on whether the article is intended to be worn by girls or boys. As will be discussed in greater detail below, the wetness indicator 39 is configured to absorb liquid, such as urine. Therefore, placement in a more forward position of the crotch region 31 may be appropriate for boys, and placement in a more central position between  
30 the legs may be appropriate for girls. Before absorption of such liquid, the

wetness indicator 39 is pliable and virtually imperceptible to the wearer, as will be discussed in greater detail below.

Although the wetness indicator 39 of the present invention is illustrated in Fig. 1 as being used in toilet training pants 21, the wetness indicator  
5 may also be used in conjunction with other garments and/or absorbent articles, such as underwear, diapers, and washable or reusable absorbent articles such as woven training pants, absorbent swim pants, plastic training pants, and the like. Further, although discussed primarily in the context of toilet training for children, it should be understood that the present invention is applicable to adult personal  
10 care products such as absorbent incontinence undergarments and the like. The wetness indicator 39 may either be built directly into the article during manufacture or may be formed independently and attached to any of the aforementioned articles by the consumer. If the wetness indicator 39 is built directly into the article during manufacture, the wetness indicator may be  
15 optionally releasably attached so the consumer can remove the wetness indicator if desired.

As illustrated in Fig. 2, a first embodiment of the wetness indicator 39 of the present invention is sized and shaped for positioning between the leg openings 27 of the pants 21. The training pants in Fig. 2 are depicted partially  
20 disassembled and unfolded to a flat position. The lateral edges 45 of the pants 21 are disconnected, exposing the flattened inner surface 36 of the pants, or the portion of the pants facing the wearer when the garment is worn. The wetness indicator 39 is positioned relative the inner surface 36 for alerting the wearer when the pants become sufficiently wet with liquid. Typically, the wetness  
25 indicator 39 is placed between the inner surface 36 and outer surface 37 (Fig. 1) to be hidden within the pants 21, such that the pliable wetness indicator is substantially imperceptible to the wearer before urination. However, those skilled in the art will appreciate the wetness indicator 39 may be positioned anywhere in the article where it is likely to become wet and be perceived by a wearer.

In one embodiment, the wetness indicator 39 is generally elongate, and remains elongate upon absorption of a preselected amount of liquid, as will be discussed in greater detail below. Although other orientations are contemplated as being within the scope of the invention, the wetness indicator 39 of one embodiment is oriented generally laterally within the garment, such that the longest dimension of the wetness indicator lies substantially parallel to a lateral axis A of the garment which extends between the leg openings 27. The periphery of the wetness indicator 39 of this embodiment is also generally rectangular in cross-section before absorption of the preselected amount of liquid, and after absorption, the wetness indicator becomes generally rounded. It is also contemplated that the wetness indicator 39 of the present invention may be formed in a shape other than a rectangle, without departing from the scope of the present invention.

Turning to the specific features of the wetness indicator 39, Figs. 3 and 4 illustrate one embodiment. The wetness indicator 39 comprises a liquid permeable enclosure 51 having a liquid absorbent body 55 therein. Generally, such a body 55 comprises a thin sheet material laid over itself at least once to form at least two folds. In one embodiment, the absorbent body 55 is formed from thin sheet material fan folded longitudinally multiple times (e.g., two times) along multiple longitudinal fold lines 59 (Fig. 4) to form a multifold structure. Such a fan folded structure enhances the strength of the absorbent body 55 because each fold of material will act to support adjacent folds, further magnifying the expansive pressure within the enclosure 51. As such, the overall strength and stiffness of the absorbent body 55 increases in the direction of the fold line. The absorbent body 55 may have at least one longitudinal fold line, thereby forming at least two folds of absorbent sheet material. By varying the number of fold lines and the width of the folds, differently sized and shaped absorbent bodies 55 are possible. In one embodiment, the outer cross-section of the wetness indicator is generally rectangular when dry, expanding to a roughly oval shape after absorption, and having a width W less than four times its height H upon

absorption of the preselected amount of liquid. For example, a square portion of material 6.4 centimeters (cm) per side and 0.065 cm thick is folded approximately in thirds to provide an absorbent body 55 having a width W of about 2.1 cm, a height H of about 0.195 cm and a length L of about 6.4 cm. The body 55 may be otherwise formed to facilitate expansion upon absorption of a preselected amount of liquid such as by being for placement within the enclosure 51. Other materials requiring no folds are also contemplated as within the scope of the present invention.

It is desirable that the absorbent body 55 be formed from a high absorbency under load (AUL) material. Although the absorbent body 55 may be made from other materials without departing from the scope of the present invention, in one embodiment the body is an Ultra Thin Absorbent (UTA) material comprising about fifty percent superabsorbent material and about fifty percent wood pulp and having a weight of about 225 grams per square meter (gsm) at a thickness of about 0.65 millimeter. One such UTA material can be produced using an online process such as described in U.S. Application number 09/939,061, entitled "Thin, High Capacity Absorbent Structure and Method for Producing Same," filed August 24, 2001, by Sawyer, et al., which claims priority from U.S. Provisional Application number 60/256,016, filed December 20, 2000, both of which are hereby incorporated by reference. In addition, U.S. Patent Nos. 5,147,343 (Kellenberger) and 5,601,542 (Melius et al.) describe other processes for producing UTA material. An alternate material is available from EAM Corporation of Jessup, Georgia, under the trademark NovaThin® material. Although other materials may be used to form the enclosure 51 without departing from the scope of the present invention, in one embodiment the liquid permeable enclosure is formed from 20 gsm spunbond nonwoven available from Kimberly-Clark Corporation, Neenah, Wisconsin. Such material may also be surface treated with about 0.45 weight percent of a surfactant mixture, such as AHCOVEL® N-62 chemical, available from Uniqema Inc., a division of ICI of New Castle, Delaware, or such as a surface treatment with an active ratio of about 3:1

of GLUCOPON® 220UP chemical, available from Cognis Corp. of Ambler, Pennsylvania. The surfactant may be applied to the entire surface of the spunbond nonwoven material, or it may be selectively applied to particular surface portions, such as to a surface portion facing the body. It is contemplated  
5 that the enclosure 51 could also include liquid impermeable portions, such as those portions positioned away from the wearer without departing from the scope of the present invention.

When liquid flows through the liquid permeable enclosure 51 of the wetness indicator 39 and contacts the absorbent body 55, the liquid is absorbed  
10 by the body. Capillary, osmotic and absorptive forces draw the liquid into the wetness indicator 39. This absorption process helps draw liquid away from the skin of the wearer. As the wetness indicator 39 absorbs the liquid, the absorbent body 55 within the enclosure 51 begins swelling. When dry, the wetness indicator 39 is generally soft, pliable and cloth-like with a first stiffness similar to the other  
15 portions of the pants 21, making the presence of the wetness indicator 39 generally imperceptible to the wearer. The pliable wetness indicator 39 allows the thighs to move freely and easily compress the wetness indicator 39.

Once liquid is present in the pants 21 and the absorbent body 55 begins absorbing liquid, the absorbent body swells within the enclosure 51. Upon  
20 absorption of a preselected amount of liquid, the absorbent body 55 applies hydraulic pressure against the interior of the enclosure 51. Because the unrestrained saturated volume of the absorbent body 55 is greater than the volume of the enclosure 57, the liquid permeable enclosure limits expansion of the absorbent body, thereby stiffening the wetness indicator 39. As more liquid is  
25 absorbed by the body 55, the wetness indicator 39 becomes stiffer. Once the wetness indicator 39 absorbs the preselected amount of liquid, the wetness indicator reaches a second stiffness greater than the first stiffness. Such a stiffness provides a resistance to bending that may be readily perceived by the wearer.



Although the wetness indicator 39 may have other stiffnesses without departing from the scope of the present invention, in one configuration, tested previously and described below, the wetness indicator has a second stiffness about eleven times greater, on average, than its first stiffness. In  
5 another configuration, tested previously and described below, the second stiffness is about fourteen times greater, on average, than its first stiffness. The method for obtaining these stiffness measurements is described in the experiments detailed below. An effective wetness indicator 39 should have a second stiffness at least about five times greater than its first stiffness.

10 For example, a wetness indicator 39 with an average dry length of about 11.5 cm, an average dry width of about 2.0 cm and an average dry thickness of about 0.5 cm and composed of the materials described herein was used. Although the second stiffness may be measured upon absorption of a  
15 different amount of liquid without departing from the scope of the present invention, in one embodiment the second stiffness is measured upon absorption of about 33 grams of urine. However, those skilled in the art will appreciate that the amount of urine absorbed by the body 55 in actual use varies depending upon the size of the wetness indicator 39 and the materials used. In other words, the stiffness may be different in actual use.

20 The enclosure 51 of Figs. 3 and 4 limits expansion of the absorbent body 55 in order for the enclosure to reach the second stiffness. If the liquid permeable enclosure 51 were too expandable, absorption of the preselected amount of liquid would simply expand the wetness indicator 39 without causing it to lose some of its pliability. In use, the pants 21 can be designed with the  
25 wetness indicator 39 positioned for resisting movement against the inner thighs of the wearer. Such resistive force exerted by the wetness indicator 39 upon the inner thighs is not large, but rather gently resists leg movement on the inside of the legs of the wearer such that the wearer perceives a resistive pressure, which he may learn to associate with urination. To further enhance the signaling  
30 properties of the wetness indicator 39, the liquid permeable enclosure 51 can be

tightly wrapped about the liquid absorbent body 55. Wrapping the enclosure 51 tightly about the absorbent body 55, lowers the expandability of the absorbent body and decreases the amount of liquid required for the wetness indicator 39 to reach its second stiffness. The absorbent body 55 must not be wrapped too tightly, however, or the first stiffness of the wetness indicator 39 before absorbing liquid will be too great.

Furthermore, it is important that the preselected amount of liquid remain within the enclosure 51 even under outside pressure, such as applied by the leg of the wearer. If wearer movement forces liquid from the absorbent body 55 and out of the enclosure 51, the ability of the wearer to perceive a stiffened wetness indicator 39 decreases. Because the wearer may be active at the time of urination, the ability of the wetness indicator 39 to resist outside forces is key. If the amount of liquid in the enclosure 51 remains above the preselected amount, the hydraulic pressure within the enclosure, and therefore the stiffness of the wetness indicator 39, may be maintained continually for a sustained and perceptible indication that urination has occurred. Forming the absorbent body from an AUL material that resists releasing liquid, even under pressure.

Fig. 5 depicts a second embodiment of the training pants 21 of the present invention in which two elongate wetness indicators 39 extend parallel to one another within the training pants 21. Although one wetness indicator 39 may sufficiently signal the wearer when urination has occurred, it is envisioned additional wetness indicators may further enhance the signal to the wearer. These wetness indicators 39 may be necessary for larger or older children with larger legs, who may find the resistive force provided by a single wetness indicator provides insufficient resistive force for perception. Further, the presence of two wetness indicators 39 permits one wetness indicator to be positioned where it is more likely to become wet upon urination by boys and one wetness indicator to be positioned where it is more likely to become wet upon urination by girls, thereby compensating for differences between the wetting patterns of boys and girls.

Fig. 6 illustrates a third embodiment of the present invention. The third embodiment of the training pants 21 includes a wetness indicator 39 having a large width W compared to its length L. For instance, the wetness indicator 39 in one embodiment has a width W between about one-fourth its length L and about three-fourths its length upon absorption of the preselected amount of liquid. Because the wetness indicator 39 has a large width W, it may be capable of absorbing more liquid than the wetness indicators of the first and second embodiments described above. Thus, it is envisioned that the wetness indicator 39 may be the only absorbent wetness indicator used in the training pants 21 of the third embodiment. Because such a wetness indicator 39 is capable of absorbing more liquid, it may provide a larger resistive pressure to the wearer due to its size.

Figs. 7 and 8 depict a fourth embodiment of the present invention. Here, the training pants 21 include a liquid permeable enclosure 51 that has at least two chambers 65. Each chamber 65 contains a separate absorbent body 55 for absorbing liquid. In addition, each of the chambers 65 acts independently from the other chambers. In one embodiment, the chambers 65 are similarly sized and shaped, although differently sized and shaped chambers are also contemplated as being within the scope of the present invention. For instance, in the preferred embodiment, the chambers 65 are generally elongate and are oriented substantially parallel to each other. Such parallel chambers 65 act in concert by resisting flexure together against the legs of the wearer.

The chambers 65 are formed within the training pants 21 in a novel way. The enclosure 51 comprises a liquid permeable lining 69, which forms the inner surface 36 of the pants 21, and a base layer 73 bonded to one another along a series of parallel, spaced-apart seams 77, forming the chambers 65. These seams 77 may be formed by sonic bonding, with an adhesive or using any other conventional sealing process capable of forming seams between the lining 69 and the base layer 73. End portions 83 of the chambers 65 are also sealed (Fig. 7). Wetness indicators 39 having fewer or more chambers 65 are

contemplated as being within the scope of the present invention, and the number and orientation of the chambers shown in Figs. 7 and 8 are exemplary only.

As will be appreciated by those skilled in the art, the enclosure 51 described above may be an osmotic membrane and the absorbent body 55 may be a solution, a mixture, or a gel without departing from the scope of the present invention.

#### Experiment 1

An experiment was conducted to determine the change in stiffness of the wetness indicator from its first stiffness when dry to its second stiffness upon absorption of the preselected amount of liquid. The experiment entailed the use of ten sample wetness indicators having an average dry length of about 11.5 cm, an average dry width of about 2.0 cm and an average dry thickness of about 0.5 cm (not including the sonic seal about the edge as described below). The samples exhibited an average dry weight of about 2.6 grams. The samples were each formed as a liquid permeable enclosure having a liquid absorbent body therein. The liquid permeable enclosure comprised 20 gsm spunbond polyethylene available from Kimberly-Clark Corporation of Neenah, Wisconsin. The spunbond polyethylene was surface treated with about a 0.45 weight percent surfactant mixture containing AHCOVEL® N-62 chemical and about a 3:1 active ratio of GLUCOPON® 220UP chemical. The liquid absorbent body comprised about ten percent Kraton® G2740X polymer, available from Kraton Polymers U.S. LLC of Houston, Texas, sixty percent Favor® SXM 880 Super Absorbent Material from Stockhausen, Inc. of Greensboro, North Carolina, and thirty percent Sulfatate-HJ-FA Kraft, Southern Hardwood Pulp from Rayonier, Inc. of Jacksonville, Florida. The liquid absorbent body was generally formed as a sheet-like material 5 cm wide and 11 cm long, fan folded lengthwise into thirds and placed inside the liquid permeable enclosure. To help the absorbent body hold its shape, an adhesive transfer tape (Model No. 922XL, 1.3 cm wide, 0.05 millimeter thick adhesive transfer tape from 3M, Inc. of St. Paul, Minnesota) was

placed between the outermost layer of the absorbent body and the remainder of the absorbent body, to retain the body in its folded configuration. In addition, the material of the liquid permeable enclosure was sonically bonded to itself for about 0.1 seconds at a pressure of 150 kiloPascals on a Branson 920 Sonic Bonder, available from Branson Ultrasonics, Inc. of Danbury, Connecticut, forming an enclosure for the absorbent body.

For each of the ten samples tested, the sample was placed across a pair of upright supports spaced 5 cm apart with about 4 cm of each end of the wetness indicator extending over each support. The supports were placed upon a tared scale so that additional vertical loads could be recorded. A testing probe having a width greater than the width of the wetness indicator and a thickness of 0.2 cm was then pressed downward upon the wetness indicator midway between the supports, thereby bending the wetness indicator and deflecting the center of the wetness indicator downward. The probe deflected the wetness indicator about 1.2 cm down from the initial horizontal position and a reading was recorded from the scale. An increase in such a reading beyond the weight of the supports and the wetness indicator indicated the force required to bend the wetness indicator, or the relative stiffness of the wetness indicator.

Once the ten samples were deflected in their dry condition, the samples were each tested again after soaking for five minutes in a 0.9% by volume Aqueous Solution Isotonic Saline (i.e., Sodium Chloride) available from Ricca Chemical Company of Arlington, Texas. The saline solution served as an approximation of urine. The five minute soak time ensured adequate saturation of the sample. After absorption, each sample was drained for one minute on a paper towel. In the saturated condition, the length and width dimensions of the wetness indicator remained unchanged, about 11.5 cm by about 2.9 cm, respectively, while the thickness of the wetness indicator increased to about 2.0 cm. In addition, the cross-sectional shape of the wetness indicator changed from a flattened rectangle to a generally rounded shape. The sample was then placed

upon the supports for the same 1.2 cm deflection noted above, again recording the load on the scale during the deflection.

On average, the load recorded for the ten dry samples during deflection was 36 grams. Subtracting the average weight of the wetness indicators themselves, 2.6 grams, this portion of the experiment indicated that a load of about 33 grams was required to deflect the wetness indicator about 1.2 cm downward from the initial horizontal position. In contrast, the load recorded for the same ten samples after absorption indicated an average load during deflection of 405 grams. Subtracting the average weight of the wetness indicators after absorption, 25 grams, the deflection load for the wetness indicator was 380 grams, on average. Thus, after absorption of liquid, the wetness indicator described above is over eleven times stiffer in bending than in its dry condition ( $380/33 = 11.5$ ). As used herein, "stiffness" means the force exerted upon the wetness indicator divided by the deflection. Here, where the deflection of each test was identical, the definition of stiffness is directly related to the recorded force. This experiment validated the assertion that the stiffness of the wetness indicator increased after absorption of liquid.

### Experiment 2

An experiment was conducted to determine the change in stiffness of another wetness indicator from its first stiffness when dry to its second stiffness upon absorption of the preselected amount of liquid. The deflection experiment was essentially the same as noted above, except that the wetness indicator itself was formed differently. Here, the liquid absorbent body was formed from a sheet-like material 3.8 cm wide and 11 cm long, folded lengthwise into half and positioned inside the liquid permeable enclosure. The overall size of the wetness indicator was 11.5 cm long, 2.0 cm wide and 0.3 cm thick (not including the sonic seal around the edge). In the saturated condition, the length dimension of the wetness indicator remained unchanged, about 11.5 cm, while the thickness of the wetness indicator increased to about 1.5 cm and the width decreases to about 1.5

cm. In addition, the cross-sectional shape of the wetness indicator changed from a flattened rectangle to a more rounded shape, as with the wetness indicator of the first experiment.

On average, the load recorded for the ten dry samples during the 1.2 cm downward deflection from the initial horizontal position was 16 grams. Subtracting the average weight of the wetness indicators themselves, 2.2 grams, this experiment indicated a load of about 14 grams was required to deflect the wetness indicator in a dry condition about 1.2 cm. In contrast, the load recorded for the same ten samples after absorption indicated an average load during deflection of 223 grams. Subtracting the average weight of the wetness indicators after absorption, 22 grams, the deflection load for the wetness indicator was 201 grams, on average. Thus, after absorption of liquid, the wetness indicator described above was over fourteen times stiffer in bending than in its dry condition ( $201/14 = 14.4$ ). Therefore, a wetness indicator should provide a second stiffness that is at least about five times greater than its first stiffness. More particularly, the second stiffness is between about five and about twenty-five times greater than the first stiffness. Preferably the second stiffness is between about ten and about fifteen times greater than the first stiffness.

Comparing the results of experiments 1 and 2, one skilled in the art would readily understand how to create a wetness indicator of varying stiffness by altering the size, materials and shape of the experimental wetness indicators. The wetness indicators disclosed in experiments 1 and 2 are included for demonstrative purposes only and should not be construed to limit the scope of the present invention. For example, wetness indicators could easily be made longer, shorter, thicker, thinner, wider, narrower or in a different configuration altogether without departing from the scope of the present invention.

When introducing elements of the present invention or the preferred embodiment(s) thereof, the articles "a", "an", "the", and "said" are intended to mean that there are one or more of the elements. The terms "comprising,"

“including”, and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements.

As various changes could be made in the above constructions without departing from the scope of the invention, it is intended that all matter  
5 contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206